CKEditor profile for *Advanced Editing*

EDIT REMOVE

BASIC SETUP

- [x] Enabled by default
  The default editor state for users having access to this profile. Users are able to override this state if the next option is enabled.
- [ ] Allow users to choose default
  If allowed, users will be able to choose their own editor default state in their user account settings.
- [x] Show *enable/disable rich text* toggle link
  Whether or not to show the *enable/disable rich text* toggle link below a textarea. If disabled, the user setting or global default is used (see above).

Interface language
English

BUTTONS AND PLUGINS

[x] Bold	[x] Italic	[ ] Underline
[x] Strike-through	[x] Align left	[x] Align center
[x] Align right	[ ] Justify	[x] Bullet list
[x] Numbered list	[ ] Outdent	[x] Indent
[ ] Undo	[ ] Redo	[x] Link
[ ] Unlink	[ ] Anchor	[x] Image
[ ] Forecolor	[ ] Backcolor	[x] Superscript
[x] Subscript	[x] Blockquote	[x] Source code
[x] Horizontal rule	[ ] Cut	[ ] Copy
[x] Paste	[ ] Paste Text	[ ] Paste from Word
[ ] Show blocks	[ ] Remove format	[x] Character map
[ ] HTML block format	[x] Font	[x] Font size
[x] Font style	[ ] Table	[ ] Select all
[ ] Search	[ ] Replace	[ ] Flash
[x] Smiley	[ ] Div container	[ ] iFrame
[ ] Maximize	[x] Check spelling	[x] Check spelling as you type
[ ] About	[x] Teaser break	

EDITOR APPEARANCE

Toolbar location
Top
This option controls whether the editor toolbar is displayed above or below the editing area.

Button alignment
Left
This option controls the alignment of icons in the editor toolbar.

Path location
Bottom
Where to display the path to HTML elements (i.e. `body > table > tr > td`).

- [x] Enable resizing button
  This option gives you the ability to enable/disable the resizing button. If enabled, the Path location toolbar must be set to "Top" or "Bottom" in order to display the resize icon.

CLEANUP AND OUTPUT

- [x] Verify HTML
  If enabled, potentially malicious code like `<HEAD>` tags will be removed from HTML contents.
- [ ] Preformatted
  If enabled, the editor will insert TAB characters on tab and preserve other whitespace characters just like a PRE element in HTML does.
- [x] Convert <font> tags to styles
  If enabled, HTML tags declaring the font size, font family, font color and font background color will be replaced by inline CSS styles.
- [x] Remove linebreaks
  If enabled, the editor will remove most linebreaks from contents. Disabling this option could avoid conflicts with other input filters.
- [ ] Apply source formatting
  If enabled, the editor will re-format the HTML source code. Disabling this option could avoid conflicts with other input filters.
- [x] Force cleanup on standard paste
  If enabled, the default paste function (CTRL-V or SHIFT-INS) behaves like the "paste from word" plugin function.

CSS

Block formats
p,address,pre,h2,h3,h4,h5,h6,div
Comma separated list of HTML block formats. Possible values: `p,h1,h2,h3,h4,h5,h6,div,blockquote,address,pre,code,dt,dd`.

Editor CSS
Use theme CSS
Defines the CSS to be used in the editor area.
Use theme CSS - loads stylesheets from current site theme.
Define CSS - enter path for stylesheet files below.
Editor default CSS - uses default stylesheets from editor.

CSS path

If "Define CSS" was selected above, enter path to a CSS file or a list of CSS files separated by a comma.
Available tokens: `%b` (base path, eg: /), `%t` (path to theme, eg: `themes/garland`)
Example: `css/editor.css,/themes/garland/style.css,%b%t/style.css,http://example.com/external.css`

CSS classes

Optionally define CSS classes for the "Font style" dropdown list.
Enter one class on each line in the format: `[title]=[class]`. Example: My heading=header1
If left blank, CSS classes are automatically imported from all loaded stylesheet(s).

Save